

AD

SPECIAL PUBLICATION ARCCB-SP-98005

**INDEX TO BENET LABORATORIES
TECHNICAL REPORTS - 1997**

R. D. NEIFELD

APRIL 1998



**US ARMY ARMAMENT RESEARCH,
DEVELOPMENT AND ENGINEERING CENTER
CLOSE COMBAT ARMAMENTS CENTER
BENÉT LABORATORIES
WATERVLIET, N.Y. 12189-4050**



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

19980505 079

DTIC QUALITY INSPECTED 4

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DESTRUCTION NOTICE

For classified documents, follow the procedures in DoD 5200.22-M, Industrial Security Manual, Section II-19 or DoD 5200.1-R, Information Security Program Regulation, Chapter IX.

For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

For unclassified, unlimited documents, destroy when the report is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1998		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE INDEX TO BENET LABORATORIES TECHNICAL REPORTS - 1997				5. FUNDING NUMBERS N/A	
6. AUTHOR(S) R.D. Neifeld					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-SP-98005	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This is a compilation of technical reports published by Benet Laboratories during 1997.					
14. SUBJECT TERMS Benet Laboratories, Technical Publications, Bibliographies, Abstracts, Document Control Data				15. NUMBER OF PAGES 44	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

TABLE OF CONTENTS

	<u>Page</u>
LIST OF REPORTS	1
AUTHOR INDEX	5
SUBJECT INDEX	9
AD NUMBERS	17
REPORT DOCUMENTATION PAGES	19

TECHNICAL REPORTS 1997

REPORT NUMBER	TITLE	AUTHOR	DATE
ARCCB-TR-97001	Use of Electromagnetic Coil Launcher to Increase Muzzle Velocity of Conventional Cannons	P.M. Vottis M. Cipollo E. Kathe Z. Zabar E. Levi L. Birenbaum	Jan 1997
ARCCB-TR-97002	Electron Transport in Highly Textured Metal Films Grown by Partially Ionized Beam Deposition	S.R. Soss B. Gittleman K.E. Mello T.-M. Lu S.L. Lee	Jan 1997
ARCCB-TR-97003	Wire EDM Fatigue Study with Application to Multi-Lug Breech Mechanisms	V.J. Olmstead S. Tauscher	Jan 1997
ARCCB-TR-97004	Stress Concentration, Stress Intensity, and Fatigue Lifetime Calculations in Autofrettaged Tubes Containing Axial Perforations Within the Wall	A.P. Parker S.N. Endersby T.J. Bond J.H. Underwood S.L. Lee J. Higgins	Feb 1997
ARCCB-TR-97005	Thermochemical Erosion Modeling of Original M242/M919 Gun System	S. Sopok G. Pflagl P. O'Hara S. Dunn D. Coats	Feb 1997
ARCCB-TR-97006	Design of Passive Vibration Absorber to Reduce Terrain-Induced Gun Barrel Vibration in the Frequency Domain	E.L. Kathe	Feb 1997
ARCCB-TR-97007	Fatigue Analysis of a Vessel Experiencing Pressure Oscillations	E. Troiano J.H. Underwood A. Scalise G.P. O'Hara D. Crayon	Mar 1997
ARCCB-TR-97008	Hydrogen-Induced Cracking Tests of High-Strength Steels and Nickel-Iron Base Alloys Using the Bolt-Loaded Specimen	G.N. Vigilante J.H. Underwood D. Crayon S. Tauscher T. Sage E. Troiano	Mar 1997

TECHNICAL REPORTS 1997

ARCCB-MR-97009	Ambient Temperature Testing of Metallic Materials Exposed to Propellant Combustion Environments Containing Hydrogen	G.N. Vigilante P.J. Cote J.H. Underwood	Mar 1997
ARCCB-TR-97010	Scaling Analysis of Thermographic Images Using Neural Networks	M.A. Johnson L.V. Meisel	Apr 1997
ARCCB-TR-97011	Erosion Modeling of the 120-mm M256/M829A2 Gun System	S. Sopok P. O'Hara P. Vottis G. Pflegl C. Rickard R. Loomis	Apr 1997
ARCCB-TR-97012	Design and Validation of a Gun Barrel Vibration Absorber	E.L. Kathe	May 1997
ARCCB-TR-97013	Laboratory Characterization of Prototype Crusader 155-mm XM297 Test Cannon #1	M.J. Audino J.H. Underwood E.J. Hyland J.A. Neese D.J. Corrigan K.D. Olsen	May 1997
ARCCB-SP-97014	Index to Benet Laboratories Technical Reports - 1996	R.D. Neifeld	Jun 1997
ARCCB-TR-97015	Fatigue Reclamation: The Concept of Self-Healing	E. Troiano P.J. Cote G.N. Vigilante	Jun 1997
ARCCB-TR-97016	Modification of ASTM Standard E1681 on Environmental Cracking to Include Bolt-Load Specimen Testing	J.H. Underwood W.A. VanDerSluys G.N. Vigilante	Jul 1997
ARCCB-TR-97017	Thermochemical Erosion Modeling of the 25-mm M242/M791 Gun System	S. Sopok P. O'Hara G. Pflegl S. Dunn D. Coats	Jul 1997
ARCCB-TR-97018	Dynamic Measurements on the 120-mm Mortar Buffer Housing	C.I. Gutierrez M.P. Rivera	Aug 1997
ARCCB-TR-97019	Residual Stress in Swage Autofrettaged Cylinders with Axial Semi-Circular Mid-Wall Cooling Channels	S.L. Lee J. Neese E. Hyland	Sep 1997

TECHNICAL REPORTS 1997

ARCCB-TR-97020	Influence of the Bauschinger Effect on Residual Stress and Fatigue Lifetimes in Autofrettaged Thick-Walled Cylinders	A.P. Parker J.H. Underwood	Sep 1997
ARCCB-TR-97021	Hydrogen Cracking During Service of High Strength Steel Cannon Components	J.H. Underwood E. Troiano G.N. Vigilante A.A. Kapusta S. Tauscher	Sep 1997
ARCCB-TR-97022	Performance Assessment of a Synergistic Gun Barrel Vibration Absorber During Bump-Course Testing	E.L. Kathe	Sep 1997
ARCCB-TR-97023	Modal Analysis of Mortar Baseplates	M.P. Rivera E. Eisler C.I. Gutierrez	Nov 1997
ARCCB-TR-97024	Thermal Effects of a Hot Weapon on High Explosive Projectiles	C.A. Morales III	Nov 1997
ARCCB-TR-97025	Modeling of Erosive Combustion Products Affecting the 120-mm M256/M829A2 Gun System	S. Sopok P. O'Hara	Nov 1997

AUTHOR INDEX 1997

AUTHOR	REPORT NUMBER
Audino, M.J.	ARCCB-TR-97013
Birenbaum, L.	ARCCB-TR-97001
Bond, T.J.	ARCCB-TR-97004
Cipollo, M.	ARCCB-TR-97001
Coats, D.	ARCCB-TR-97005 ARCCB-TR-97017
Corrigan, D.J.	ARCCB-TR-97013
Cote, P.J.	ARCCB-MR-97009 ARCCB-TR-97015
Crayon, D.	ARCCB-TR-97007 ARCCB-TR-97008
Dunn, S.	ARCCB-TR-97005 ARCCB-TR-97017
Eisler, E.	ARCCB-TR-97023
Endersby, S.N.	ARCCB-TR-97004
Gittleman, B.	ARCCB-TR-97002
Gutierrez, C.I.	ARCCB-TR-97018 ARCCB-TR-97023
Higgins, J.	ARCCB-TR-97004
Hyland, E.J.	ARCCB-TR-97013 ARCCB-TR-97019
Johnson, M.A.	ARCCB-TR-97010
Kapusta, A.A.	ARCCB-TR-97021
Kathe, E.L.	ARCCB-TR-97001 ARCCB-TR-97006 ARCCB-TR-97012 ARCCB-TR-97022

AUTHOR INDEX 1997

Lee, S.L.	ARCCB-TR-97002 ARCCB-TR-97004 ARCCB-TR-97019
Levi, E.	ARCCB-TR-97001
Loomis, R.	ARCCB-TR-97011
Lu, T.-M.	ARCCB-TR-97002
Meisel, L.V.	ARCCB-TR-97010
Mello, K.E.	ARCCB-TR-97002
Morales, C.A., III	ARCCB-TR-97024
Neese, J.A.	ARCCB-TR-97013 ARCCB-TR-97019
Neifeld, R.D.	ARCCB-SP-97014
O'Hara, G.P.	ARCCB-TR-97005 ARCCB-TR-97007 ARCCB-TR-97011 ARCCB-TR-97017 ARCCB-TR-97025
Olmstead, V.J.	ARCCB-TR-97003
Olsen, K.D.	ARCCB-TR-97013
Parker, A.P.	ARCCB-TR-97004 ARCCB-TR-97020
Pflegl, G.	ARCCB-TR-97005 ARCCB-TR-97011 ARCCB-TR-97017
Rickard, C.	ARCCB-TR-97011
Rivera, M.P.	ARCCB-TR-97018 ARCCB-TR-97023
Sage, T.	ARCCB-TR-97008
Scalise, A.	ARCCB-TR-97007

AUTHOR INDEX 1997

Sopok, S.	ARCCB-TR-97005 ARCCB-TR-97011 ARCCB-TR-97017 ARCCB-TR-97025
Soss, S.R.	ARCCB-TR-97002
Tauscher, S.	ARCCB-TR-97003 ARCCB-TR-97008 ARCCB-TR-97021
Troiano, E.	ARCCB-TR-97007 ARCCB-TR-97008 ARCCB-TR-97015 ARCCB-TR-97021
Underwood, J.H.	ARCCB-TR-97004 ARCCB-TR-97007 ARCCB-TR-97008 ARCCB-MR-97009 ARCCB-TR-97013 ARCCB-TR-97016 ARCCB-TR-97020 ARCCB-TR-97021
VanDerSluys, W.A.	ARCCB-TR-97016
Vigilante, G.N.	ARCCB-TR-97008 ARCCB-MR-97009 ARCCB-TR-97015 ARCCB-TR-97016 ARCCB-TR-97021
Vottis, P.M.	ARCCB-TR-97001 ARCCB-TR-97011
Zabar, Z.	ARCCB-TR-97001

SUBJECT INDEX 1997

SUBJECT	REPORT NUMBER
Ablation	ARCCB-TR-97005 ARCCB-TR-97011 ARCCB-TR-97017
Absorbers (Materials)	ARCCB-TR-97012
Abstracts	ARCCB-SP-97014
Accuracy	ARCCB-TR-97022
Aluminum	ARCCB-TR-97002
Autofrettage	ARCCB-TR-97004 ARCCB-TR-97013 ARCCB-TR-97019 ARCCB-TR-97020
Bauschinger Effect	ARCCB-TR-97019 ARCCB-TR-97020
Bibliographies	ARCCB-SP-97014
Bolt-Load Specimens	ARCCB-TR-97016
Bores	ARCCB-TR-97004
Breech Mechanisms	ARCCB-TR-97003
Bump-Course Testing	ARCCB-TR-97022
Burst Testing	ARCCB-TR-97013
Cannons	ARCCB-TR-97006 ARCCB-TR-97012 ARCCB-TR-97022 ARCCB-TR-97024
Castings	ARCCB-TR-97018
Chromium	ARCCB-TR-97005 ARCCB-TR-97011 ARCCB-TR-97017
Combustion Gases	ARCCB-MR-97009

SUBJECT INDEX 1997

Combustion Products	ARCCB-TR-97025
Compound Cylinders	ARCCB-TR-97019
Computerized Simulation	ARCCB-TR-97005
Copper	ARCCB-TR-97002
Cracking (Fracturing)	ARCCB-TR-97004 ARCCB-TR-97007 ARCCB-TR-97008 ARCCB-MR-97009 ARCCB-TR-97015 ARCCB-TR-97016 ARCCB-TR-97020 ARCCB-TR-97021
Cylindrical Bodies	ARCCB-TR-97004 ARCCB-TR-97020
Defects (Materials)	ARCCB-TR-97018
Dynamics	ARCCB-TR-97022
Electrical Discharge Machining (EDM)	ARCCB-TR-97003
Electromagnetic Guns	ARCCB-TR-97001
Electron Transport	ARCCB-TR-97002
Environmental Cracking	ARCCB-TR-97007 ARCCB-TR-97008 ARCCB-MR-97009 ARCCB-TR-97016 ARCCB-TR-97021
Erosion	ARCCB-TR-97005 ARCCB-TR-97011 ARCCB-TR-97017 ARCCB-TR-97025
Exudation	ARCCB-TR-97024
Failure (Mechanics)	ARCCB-TR-97013
Fast Fourier Transform Analysis	ARCCB-TR-97023

SUBJECT INDEX 1997

Fatigue (Mechanics)	ARCCB-TR-97015
Fatigue Life	ARCCB-TR-97004 ARCCB-TR-97007 ARCCB-TR-97013 ARCCB-TR-97019 ARCCB-TR-97020
Fatigue Tests (Mechanics)	ARCCB-TR-97003
Finite Element Analysis	ARCCB-TR-97004 ARCCB-TR-97006 ARCCB-TR-97012 ARCCB-TR-97019 ARCCB-TR-97021 ARCCB-TR-97023
Fractals	ARCCB-TR-97010
Fracture (Mechanics)	ARCCB-TR-97004 ARCCB-TR-97016 ARCCB-TR-97020
Gas Guns	ARCCB-TR-97001
Glass Bead Cleaning	ARCCB-TR-97003
Gun Barrels	ARCCB-TR-97001 ARCCB-TR-97005 ARCCB-TR-97006 ARCCB-TR-97011 ARCCB-TR-97012 ARCCB-TR-97017 ARCCB-TR-97022 ARCCB-TR-97025
Gun Components	ARCCB-TR-97021
Gun Launchers	ARCCB-TR-97001
Gun Mounts	ARCCB-TR-97023
Gun Tubes	ARCCB-MR-97009 ARCCB-TR-97013 ARCCB-TR-97020 ARCCB-TR-97024

SUBJECT INDEX 1997

Guns	ARCCB-TR-97011 ARCCB-SP-97014
Heat Treatment	ARCCB-TR-97015
High Explosives	ARCCB-TR-97024
High Strength Steels	ARCCB-TR-97008 ARCCB-MR-97009 ARCCB-TR-97016 ARCCB-TR-97021
High Temperatures	ARCCB-TR-97007
Hoop Stress	ARCCB-TR-97007
Housings	ARCCB-TR-97018
Hybrid Cannons	ARCCB-TR-97001
Hydrogen Cracking	ARCCB-TR-97021
Hydrogen Embrittlement	ARCCB-TR-97008 ARCCB-MR-97009
Image Processing	ARCCB-TR-97010
Indexes	ARCCB-SP-97014
Iron Alloys	ARCCB-TR-97008
Low Cycle Fatigue Regime	ARCCB-TR-97007 ARCCB-TR-97015
Lugs	ARCCB-TR-97003
M107 Projectiles	ARCCB-TR-97024
M1A1 Tanks	ARCCB-TR-97022
M242 Guns	ARCCB-TR-97005 ARCCB-TR-97017
M256 Guns	ARCCB-TR-97011 ARCCB-TR-97025
M549A1 Projectiles	ARCCB-TR-97024

SUBJECT INDEX 1997

Mathematical Models	ARCCB-TR-97006
Metal Films	ARCCB-TR-97002
Modal Analysis	ARCCB-TR-97023
Modeling Codes	ARCCB-TR-97005 ARCCB-TR-97011 ARCCB-TR-97017 ARCCB-TR-97025
Monte-Carlo Method	ARCCB-TR-97002
Mortar Baseplates	ARCCB-TR-97023
Mortars	ARCCB-TR-97018
Muzzle Velocity	ARCCB-TR-97001
Neural Nets	ARCCB-TR-97010
Nickel Alloys	ARCCB-TR-97008
120-mm Mortars	ARCCB-TR-97018
Oscillations	ARCCB-TR-97007
Parallel Processing	ARCCB-TR-97010
Partially Ionized Beam Deposition	ARCCB-TR-97002
Passive Systems	ARCCB-TR-97006 ARCCB-TR-97012
Power Spectra	ARCCB-TR-97022
Pressure Amplitude	ARCCB-TR-97013
Pressure Vessels	ARCCB-TR-97007 ARCCB-TR-97021
Projectiles	ARCCB-TR-97024
Propellants	ARCCB-MR-97009
Radial Stress	ARCCB-TR-97007

SUBJECT INDEX 1997

Reclamation Concept	ARCCB-TR-97015
Reports	ARCCB-SP-97014
Residual Stress	ARCCB-TR-97004 ARCCB-TR-97007 ARCCB-TR-97019 ARCCB-TR-97020
Resistivity	ARCCB-TR-97002
Reverse Yielding	ARCCB-TR-97019
Safe Maximum Pressure Testing	ARCCB-TR-97013
Scaling Factor	ARCCB-TR-97010
Service Life Conditions	ARCCB-TR-97013
Shot Peening	ARCCB-TR-97003
Silver	ARCCB-TR-97002
Stainless Steel	ARCCB-MR-97009 ARCCB-TR-97021
Standards	ARCCB-TR-97016
Steel	ARCCB-TR-97003 ARCCB-TR-97008 ARCCB-TR-97011 ARCCB-TR-97016 ARCCB-TR-97017
Stress Concentration	ARCCB-TR-97004
Stress Corrosion	ARCCB-MR-97009
Stress Intensity Factor	ARCCB-TR-97004 ARCCB-TR-97020
Stress-Strain Relations	ARCCB-TR-97007 ARCCB-TR-97013
Stresses	ARCCB-TR-97008 ARCCB-TR-97018

SUBJECT INDEX 1997

Tank Cannons	ARCCB-TR-97006
Tank Guns	ARCCB-TR-97012
Tantalum	ARCCB-TR-97005
Technical Publications	ARCCB-SP-97014
Texture	ARCCB-TR-97002
Thermal Properties	ARCCB-TR-97024
Thermochemistry	ARCCB-TR-97005 ARCCB-TR-97017 ARCCB-TR-97025
Thermography	ARCCB-TR-97010
Threshold Effects	ARCCB-TR-97008
Vibration	ARCCB-TR-97006 ARCCB-TR-97012 ARCCB-TR-97022 ARCCB-TR-97023
Wire	ARCCB-TR-97003
XM297 Test Cannon	ARCCB-TR-97013

AD NUMBERS 1997

REPORT NUMBER

AD NUMBER

ARCCB-TR-97001

A322 875

ARCCB-TR-97002

A323 329

ARCCB-TR-97003

A323 801

ARCCB-TR-97004

A323 691

ARCCB-TR-97005

A323 941

ARCCB-TR-97006

A323 756

ARCCB-TR-97007

A323 827

ARCCB-TR-97008

A324 009

ARCCB-MR-97009

A324 040

ARCCB-TR-97010

A325 374

ARCCB-TR-97011

A325 610

ARCCB-TR-97012

A325 897

ARCCB-TR-97013

B225 449

ARCCB-SP-97014

B226 710

ARCCB-TR-97015

A327 052

ARCCB-TR-97016

A327 896

ARCCB-TR-97017

A328 554

ARCCB-TR-97018

B229 428

ARCCB-TR-97019

A329 516

ARCCB-TR-97020

A330 071

ARCCB-TR-97021

A330 833

ARCCB-TR-97022

B230 790

ARCCB-TR-97023

B232 204

ARCCB-TR-97024

B233 026

ARCCB-TR-97025

A337 425

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE USE OF ELECTROMAGNETIC COIL LAUNCHER TO INCREASE MUZZLE VELOCITY OF CONVENTIONAL CANNONS				5. FUNDING NUMBERS AMCMS No. 6111.01.91A1.1	
6. AUTHOR(S) P.M. Vottis, M. Cipollo, E. Kathe, Z. Zabar*, E. Levi*, and L. Birenbaum* * Polytechnic University, Brooklyn, NY					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97001	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 8th EML Symposium, Baltimore, MD, 21-24 April 1996. Published in <i>IEEE Transactions on Magnetics</i> .					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This paper describes the design and operation of an experimental hybrid cannon consisting of a 60-mm bore gas cannon using standard propellant and a traveling-wave induction accelerator. The projectile, consisting of an aluminum cylinder weighing 120 grams, is initially brought up to a speed of 600 m/s in the gas cannon. The pulsed-power stage is designed to accelerate the projectile further to a velocity of 700 m/s.					
14. SUBJECT TERMS Hybrid Cannon, Hybrid Launcher, Chemical/EM Launcher, Electromagnetic Accelerator, Electromagnetic Launcher				15. NUMBER OF PAGES 16	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE ELECTRON TRANSPORT IN HIGHLY TEXTURED METAL FILMS GROWN BY PARTIALLY IONIZED BEAM DEPOSITION			5. FUNDING NUMBERS AMCMS No. 6111.01.91A1.1	
6. AUTHOR(S) S.R. Soss (RPI, Troy, NY), B. Gittleman (RPI), K.E. Mello (RPI), T.-M. Lu (RPI), and S.L. Lee				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97002	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the Materials Research Society Fall Conference, Boston, MA, 26 November - 1 December 1995. Published in proceedings of the conference.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) In principle, the resistivity of bulk face-centered-cubic (fcc) materials should not depend on the orientation due to the fact that the conductivity tensor is single valued. However, we show that this conclusion is not valid for thin films. Deposition of highly oriented aluminum, silver, and copper films on amorphous substrates using the partially ionized beam (PIB) technique exhibits a resistivity that is strongly correlated with the texture, i.e., the tighter the texture, the lower the film resistivity. We model the film as an array of grains whose grain boundaries can be considered as delta function potentials for electron scattering, and the strength of the potentials can be calculated from the measured resistivity of the films. On the other hand, the fiber texture distribution of the films is obtained from X-ray pole figure measurements, and Monte-Carlo simulations are then performed using these data to determine the average dislocation density at the grain boundaries due to the grain-to-grain crystallographic mismatch. We show that the transmittance coefficient for electron scattering, and therefore, the film resistivity, is a monotonically increasing function of the average dislocation density. We, therefore, conclude that the structure of grain boundaries in a thin film provides the necessary mechanism by which the resistivity of an fcc cubic metal can depend on the texture.				
14. SUBJECT TERMS Partially Ionized Beam Deposition, Aluminum Films, Silver Films, Copper Films, Resistivity, Monte-Carlo Simulation, Electron Transport			15. NUMBER OF PAGES 11	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE WIRE EDM FATIGUE STUDY WITH APPLICATION TO MULTI-LUG BREECH MECHANISMS				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. W16H1F531	
6. AUTHOR(S) V.J. Olmstead and S. Tauscher					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97003	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A fatigue study was conducted to evaluate wire electrical discharge machining (EDM) as a manufacturing method for the production of the intricate lug geometry on multi-lug breech mechanisms. The wire EDM process produces a thin surface layer of recast material that was found to have an adverse effect on specimen fatigue life. Removal of the recast layer is recommended on highly stressed critical components. Unidirectional bending fatigue tests were performed utilizing notched rectangular test specimens made from ASTM A723 steel material. The fatigue tests compared wire EDM prepared surfaces to those produced by the conventional drilling and honing process. The effects of multiple EDM passes and post-processing techniques such as bead blast cleaning, shot peening, and mechanical overloading were investigated. The recast layer was found to have a significant detrimental effect on specimen fatigue lives. Fatigue life reductions of 20 to 40 percent were observed. The deleterious effect on fatigue increases as the applied stress decreases. The post-processing techniques improved lives but they were generally inferior to those that were conventionally machined and treated with the same process. In limited testing, the combination of glass bead cleaning and mechanical overloading provided "significant" improvement in life compared to either process applied individually.					
14. SUBJECT TERMS EDM Recast Layer, Fatigue, Glass Bead Clean, Gun Steel, Multi-Lug Breech Mechanisms, Overload, Shot Peen, Wire EDM				15. NUMBER OF PAGES 29	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE STRESS CONCENTRATION, STRESS INTENSITY, AND FATIGUE LIFETIME CALCULATIONS IN AUTOFRETTAGED TUBES CONTAINING AXIAL PERFORATIONS WITHIN THE WALL				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. TU5A5F361ABJ	
6. AUTHOR(S) Anthony P. Parker (Royal Military College of Science, Cranfield Univ., UK), Stephen N. Endersby (U. of Northumbria, UK), Timothy J. Bond (U. of Northumbria, UK), John H. Underwood, Sabrina L. Lee, and John Higgins					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97004	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the ASME Pressure Vessels and Piping Conference, Montreal, Canada, 22-26 July 1996. Published in proceedings of the conference.					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words.) Elastic, elastic-plastic, and experimental stress analyses and fatigue lifetime predictions are presented for thick cylinders containing multiple, axial holes within the wall. The holes are generally semi-elliptical (including semi-circular) and the cylinders are autofrettaged after introduction of the holes and are subsequently subjected to cyclic pressurization of the bore. Two potentially critical failure locations are identified; a fracture-mechanics based design methodology is proposed; elastic and elastic-plastic finite element (FE) analyses are undertaken. The elastic FE analysis predicts hoop stresses at the bore resulting from internal pressurization which are some 7% higher than those for the equivalent plain tube. For a given hole size and location and for nominal overstrains of 40% or greater, the residual compressive stress at the bore is reduced by approximately 15% below the value for a plain tube of the same radius ratio. Two experimental investigations are reported, one based upon X-ray diffraction, to measure residual stresses, and the other based upon radial tube slitting, to measure opening angle. They confirm most features of the residual stress profiles predicted from FE analysis, with the exception of high compressive residual stresses and stress gradients immediately adjacent to the hole boundaries. Appropriate use of the residual stress information permits prediction of tube lifetimes for cracks emanating from the bore and from the hole. For the geometry and loading under consideration, the more critical location is predicted to be the hole boundary, the lifetime for failures originating from this point being some 60% of the lifetime for cracks originating at the bore.					
14. SUBJECT TERMS Autofrettage, Crack Growth, Fatigue Cracks, Cylinders, Channels, Fracture (Materials), Fracture Mechanics, Residual Stress, Stress Concentration Factor, Stress Intensity Factor				15. NUMBER OF PAGES 15	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE THERMOCHEMICAL EROSION MODELING OF ORIGINAL M242/M919 GUN SYSTEM			5. FUNDING NUMBERS AMCMS No. 6226,24,H180.0 PRON No. 4A6B6FYK1ABJ	
6. AUTHOR(S) Samuel Sopok, George Pflagl, Peter O'Hara, Stuart Dunn*, and Douglas Coats* * Software and Engineering Associates, Inc., Carson City, NV				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97005	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 1996 JANNAF 33rd Combustion Meeting, Monterey, CA, 4-8 November 1996. Published in proceedings of the meeting.				
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The MACE gun barrel thermochemical erosion modeling code addresses wall degradations due to transformations, chemical reactions, and cracking coupled with pure mechanical erosion for the original M242/M919 gun system. This predictive tool provides gun system design information that is otherwise impractical. The A723, 0.002-inch plated chromium/A723, and 0.002-inch sputtered tantalum/A723 wall materials are evaluated for erosion using the M242 Cycle A firing scenario. This complex computer analysis is based on rigorously evaluated scientific theory that has been validated in the rocket community over the last forty years. Our gun erosion analysis includes the standard interior ballistics gun code (XNOVAKTC), the standard nonideal gas-wall thermochemical rocket code modified for guns (CCET), the standard mass addition boundary layer rocket code modified for guns (MABL), and the standard wall material ablation conduction erosion rocket code modified for guns (MACE). This analysis provides wall material erosion predictions and comparisons (ablation, conduction, and erosion profiles) as a function of time, travel (customer-selected 6-inch, 12-inch, 30-inch), and number of rounds to barrel condemnation. These original M242/M919 gun system predictions agree well with the standard wall heat transfer/temperature profile code (FDHEAT) and actual measured gun system erosion data.				
14. SUBJECT TERMS Modeling Code, Thermochemical Erosion, Erosion Predictions, Gun Barrels, Thermochemical Ablation, Mechanical Erosion, M242/M919 Gun System, Chromium, Tantalum			15. NUMBER OF PAGES 26	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE DESIGN OF PASSIVE VIBRATION ABSORBER TO REDUCE TERRAIN-INDUCED GUN BARREL VIBRATION IN THE FREQUENCY DOMAIN				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. 4A6C6FYA1ABJ	
6. AUTHOR(S) Eric L. Kathe					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97006	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 8th U.S. Army Gun Dynamics Symposium, Newport, RI, 14-16 May 1996. Published in proceedings of the symposium.					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This paper presents an applied method for the optimal design of passive vibration absorbers to reduce terrain-induced vibrations of tank cannons. The method uses a finite element model of the cannon, which was formulated using the Euler-Bernoulli transverse beam approximation. This model is then transformed to the Laplace "s" domain (transfer function form) using the MATLAB® software package. The design is optimized by assigning a scalar cost function to the frequency response of the modified barrel, which provides a metric for minimizing the design parameter space. The results indicate that the peak amplitude of the frequency response of a 1,500 Kg barrel may be cut in half by an appropriately tuned 20 Kg absorber located at the muzzle. Also, sensitivity of the design to parametric variation and modeling uncertainty is significantly reduced with Rayleigh stiffness proportional damping of the absorber in the range $0.02 \frac{N/(m/s)}{N/m}$.					
14. SUBJECT TERMS Finite Element Method, Vibration Absorber, Passive, Design, Cannon				15. NUMBER OF PAGES 20	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE FATIGUE ANALYSIS OF A VESSEL EXPERIENCING PRESSURE OSCILLATIONS			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.000 PRON No. TU5B5F261ABJ	
6. AUTHOR(S) Edward Troiano, John H. Underwood, Anthony Scalise, G. Peter O'Hara, and Daniel Crayon				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97007	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the ASTM 28th National Symposium on Fatigue and Fracture Mechanics. Saratoga, NY, 25-27 June 1996. Published in <i>ASTM STP 1321, Fatigue and Fracture Mechanics, 28th Volume</i> .				
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A pressure vessel, which was designed and tested under laboratory conditions for tens of thousands of cycles, failed in service after only a few cycles. Thousands of oscillatory pressure reversals were measured at each loading. However, the predominance of the stress amplitudes were well below the critical threshold values necessary to initiate fatigue cracking. Analysis demonstrated that the disparity between lab cycling and field loading conditions could not be explained simply by mechanical loading alone. Further investigation into the problem revealed that an extremely aggressive environment, the by-products of the internal combustion from within the pressure vessel, along with high temperatures, pressures, and other sources of high tensile loading all contributed to the short fatigue life of the vessel.				
14. SUBJECT TERMS Low-Cycle Fatigue, Pressure Oscillations, Pressure Vessels, Cumulative Damage Model, Residual Stresses, Hoop Stress, Radial Stress, Fatigue Cracks, Palmgren-Miner Rule, Environmentally-Assisted Cracking			15. NUMBER OF PAGES 16	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE HYDROGEN-INDUCED CRACKING TESTS OF HIGH-STRENGTH STEELS AND NICKEL-IRON BASE ALLOYS USING THE BOLT-LOADED SPECIMEN				5. FUNDING NUMBERS AMCMS No. 6111.01.91A1.1	
6. AUTHOR(S) G.N. Vigilante, J.H. Underwood, D. Crayon, S. Tauscher, T. Sage, and E. Troiano					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benel Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97008	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the ASTM 28th National Symposium on Fatigue and Fracture Mechanics, Saratoga Springs, NY, 25-27 June 1996. Published in <i>ASTM STP 1321. Fatigue and Fracture Mechanics, 28th Volume.</i>					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Hydrogen-induced cracking tests were conducted on high-strength steels and nickel-iron base alloys using the constant displacement bolt-loaded compact specimen. The bolt-loaded specimen was subjected to both acid and electrochemical cell environments to produce hydrogen. The materials tested were A723, Maraging 200, PH 13-8 Mo, Alloy 718, Alloy 706, and A286, ranging in yield strength from 760-1400 MPa. The effects of chemical composition, refinement, heat treatment, and strength on hydrogen-induced crack growth rates and thresholds were examined. In general, all high strength steels tested exhibited similar crack growth rates and threshold levels. In comparison, the nickel-iron base alloys tested exhibited crack growth rates up to three orders of magnitude lower than the high-strength steels tested. It is widely known that high-strength steels and nickel base alloys exhibit different crack growth rates, in part, because of their different crystal cell structure. In the high-strength steels tested, refinement and heat treatment had some effect on hydrogen-induced cracking, although strength was the predominant factor influencing susceptibility to cracking. When the yield strength of one of the high-strength steels tested was increased moderately, from 1130 MPa to 1275 MPa, the incubation times decreased by over two orders of magnitude, the crack growth rates increased by an order of magnitude, and the threshold stress intensity was slightly lower.					
14. SUBJECT TERMS Threshold Stress Intensity, Hydrogen-Induced Cracking, Hydrogen Cracking, Hydrogen Embrittlement, Environmental Fracture, Environmental Cracking, Crack Growth Rates, High-Strength Steels, Nickel-Iron Base Alloys				15. NUMBER OF PAGES 21	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE AMBIENT TEMPERATURE TESTING OF METALLIC MATERIALS EXPOSED TO PROPELLANT COMBUSTION ENVIRONMENTS CONTAINING HYDROGEN				5. FUNDING NUMBERS AMCMS No. 6111.01.91A1.100	
6. AUTHOR(S) G.N. Vigilante, P.J. Cote, and J.H. Underwood					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-MR-97009	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Combustion gases containing hydrogen can cause severe environmental degradation and cracking in the high strength steels used in gun tubes. Although the hydrogen is evolved at the elevated temperatures of combustion, the deleterious effects of hydrogen on steel are most severe near ambient temperature.					
14. SUBJECT TERMS Environmentally-Assisted Cracking, Hydrogen-Induced Cracking, Hydrogen Embrittlement, Propellants, Combustion Gases, High Strength Steels				15. NUMBER OF PAGES 5	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT III	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE SCALING ANALYSIS OF THERMOGRAPHIC IMAGES USING NEURAL NETWORKS				5. FUNDING NUMBERS AMCMS No. 6111.02.H671.1	
6. AUTHOR(S) Mark A. Johnson and Lawrence V. Meisel					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97010	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the Aerosense Conference, Orlando, FL, 20-25 April 1997. Published in proceedings of the conference.					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Sequences of thermographic images of burning residue produced by M198 155 (unicharge) test rounds fired at Yuma Proving Ground (YPG) were collected for analysis to elucidate the evolution of conditions in the breech after firing and to provide guidance in determining safe loading protocols for future autoloaders. In order to better understand the thermal environment in the breech, we are developing advanced analytical tools that can be used to quantitatively characterize sequences of thermographic images. However, for this study the calibration data required to extract the temperature profiles the YPG thermographic images for these analyses was unavailable. No analytic solution could be determined to perform the highly nonlinear reverse transformation from RGB space to intensities; therefore, a neural network was employed. Furthermore, the experimental data provided by YPG were only measurable over a restricted range of temperatures extending from approximately 80°C up to 110°C. Since the highest temperatures measured in the thermographic data did not correspond to a hazardous condition, more complex measures than simple statistical averages of the temperature had to be used. A new numerical technique represented by sparse data sets was introduced for measuring the scaling properties of single-valued surfaces in 3-space.					
14. SUBJECT TERMS Neural Networks, Scaling Analysis, Parallel Processing, Image Processing, Fractal Analysis				15. NUMBER OF PAGES 8	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE EROSION MODELING OF THE 120-MM M256/M829A2 GUN SYSTEM			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. 4A7A7FYK1ABJ	
6. AUTHOR(S) Samuel Sopok, Peter O'Hara, Patrick Vottis, George Pflegl, Christopher Rickard, and Richard Loomis (PM-TMAS, Dover, NJ)				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97011	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 1997 ADPA Gun and Ammunition Symposium, San Diego, CA, 7-10 April 1997. Published in proceedings of the conference.				
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The Benet Laboratories/Software and Engineering Associates, Inc. (SEA) gun barrel erosion modeling and design code predicts wall degradation due to transformations, chemical reactions, and cracking coupled with pure mechanical erosion for the 120-mm M256/M829A2 gun system for ambient temperature-conditioned rounds. The A723 steel and 0.005-inch high contraction (HC) chromium plated/A723 steel wall materials are evaluated for erosion. This complex computer analysis is based on rigorously evaluated scientific theory that has been validated in the rocket community over the last forty years. Our gun erosion analysis includes the standard interior ballistics gun code (XNOVAKTC), the standard nonideal gas-wall thermochemical rocket code modified for guns (CCET), the standard mass addition boundary layer rocket code modified for guns (MABL), and the standard wall material ablation conduction erosion rocket code modified for guns (MACE). In addition, bore subsurface metallographic analysis and projectile-bore finite element analysis (ABAQUS) are considered. Our overall analysis provides wall material erosion predictions and comparisons of ablation, conduction, and erosion profiles as a function of time, travel (customer-selected 27, 61, 86, 130, and 201 inches from the rear face of the tube), and number of rounds to barrel condemnation. The 120-mm M256/M829A2 gun system prediction, with significant numbers of M829A2 rounds, agrees well with the wear and erosion pattern of retired M256 gun barrels.				
14. SUBJECT TERMS Erosion Modeling, 120-mm M256/M829A2 Gun System, Gun Barrels, Chromium, Steel			15. NUMBER OF PAGES 24	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE May 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE DESIGN AND VALIDATION OF A GUN BARREL VIBRATION ABSORBER				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. 4A6C6FYA1ABJ	
6. AUTHOR(S) Eric L. Kathe					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97012	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 67th Shock and Vibration Symposium, Monterey, CA, 18-22 November 1996. Published in proceedings of the symposium.					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This paper presents an applied method for the optimal design of passive vibration absorbers to reduce terrain-induced vibrations of tank cannons. The method uses a finite element model of the cannon. The design is optimized by assigning a scalar cost function to the frequency response of the modified barrel. The results indicate that the peak amplitude of the frequency response of a 1,500 Kg barrel may be cut in half by an appropriately tuned 20 Kg absorber. Experimental validation of the results using modal impact testing are shown.					
14. SUBJECT TERMS Vibration Absorbers, Passive, Design, Cannons, Gun Barrels, Finite Element Method				15. NUMBER OF PAGES 15	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE May 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE LABORATORY CHARACTERIZATION OF PROTOTYPE CRUSADER 155-MM XM297 TEST CANNON #1			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. TU6A6F361ABJ	
6. AUTHOR(S) Michael J. Audino, John H. Underwood, Edward J. Hyland, James A. Neese, Daniel J. Corrigan, and Kenneth D. Olsen				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97013	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution limited to U.S. Government Agencies only because of test and evaluation; May 1997. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-TA, Watervliet, NY 12189-4050.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) During the design and development of weapon systems, it is imperative to evaluate prototype components for the purpose of validating theoretical calculations and predictions made earlier in the design process. This report describes strain characterization testing conducted on 155-mm XM297 Test Cannon #1 for the purpose of validating calculated strains from the swage autofrettage process, evaluating fatigue life of various midwall and outer wall geometric configurations, validating calculated strains from simulated service life conditions, determining the maximum pressure containment capability of the cannon, and finally, determining the failure mode of the cannon.				
14. SUBJECT TERMS Characterization, Autofrettage, Midwall, Service Life Conditions, Failure Mode, Pressure Amplitude, Safe Maximum Pressure, Burst Test, Coolant Groove, International Test Operating Procedures			15. NUMBER OF PAGES 91	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE INDEX TO BENET LABORATORIES TECHNICAL REPORTS - 1996				5. FUNDING NUMBERS N/A	
6. AUTHOR(S) R.D. Neifeld					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-SP-97014	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION AVAILABILITY STATEMENT Distribution limited to U.S. Government Agencies only because of specific authority; June 1997. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-O, Watervliet, NY 12189-4050.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This is a compilation of technical reports published by Benet Laboratories during 1996.					
14. SUBJECT TERMS Benet Laboratories, Technical Publications, Bibliographies, Abstracts, Document Control Data				15. NUMBER OF PAGES 56	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE FATIGUE RECLAMATION: THE CONCEPT OF SELF-HEALING				5. FUNDING NUMBERS AMCMS No. 6111.02.H611.1	
6. AUTHOR(S) E. Troiano, P.J. Cote, and G.N. Vigilante					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97015	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 14th Army Symposium on Solid Mechanics, Myrtle Beach, SC, 16-18 October 1996. Published in proceedings of the symposium.					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A simple analytical model for predicting the onset of fatigue crack initiation has been developed. The model's usefulness is based on the premise that if a component can be removed from service before fatigue crack initiation and thermally heat-treated to remove any accumulated fatigue damage, it can be placed back in service and periodically heat-treated to extend its life. Three-point bend specimens with semi-circular notches were machined from A723 steel, isothermally processed in molten salts to predetermined strength and toughness levels, and fatigue-tested in the extreme low cycle fatigue region. Because of negative preliminary findings, the concept of reclamation fatigue in the extremely low cycle fatigue regime does not appear to be a viable means for extending the overall life of components. Although technically correct, the model did not accurately predict the onset of crack initiation. The study also suggests that, although cracking was not observed in all specimens, some damage could not be eliminated by thermal treatment. Because most point defects will be eliminated by thermal treatment, it is believed that non-detectable microscopic crack growth had occurred.					
14. SUBJECT TERMS Fatigue Crack Initiation, Fatigue Reclamation, Crack Detection, Low Cycle Fatigue Regime, Heat Treatment				15. NUMBER OF PAGES 8	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE July 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE MODIFICATION OF ASTM STANDARD E1681 ON ENVIRONMENTAL CRACKING TO INCLUDE BOLT-LOAD SPECIMEN TESTING			5. FUNDING NUMBERS AMCMS No. 6111.02.H611.1	
6. AUTHOR(S) J.H. Underwood, W.A. VanDerSluys (Babcock and Wilcox, Alliance, OH), and G.N. Vigilante				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97016	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Benet Laboratories experience with environmental cracking of cannon components has been combined with the technical expertise of various participants at ASTM technical meetings and symposia to develop a modification to ASTM Standard E1681, "Test Method for Determining a Threshold Stress Intensity Factor for Environment-Assisted Cracking of Metallic Materials Under Constant Load." A bolt-loaded compact specimen has been added to the standard to allow constant displacement bolt-load tests of environmental cracking threshold. Recent investigations of environmental cracking in two cannon systems are briefly summarized, including cracking in acids used in the electroplating process and cracking due to cannon propellant gases. The modified draft of ASTM Standard E1681 is presented, including the additions to test procedure, apparatus, and stress intensity factor expressions required to perform bolt-load tests of environmental cracking threshold.				
14. SUBJECT TERMS Environmental Cracking, Fracture Mechanics, High Strength Steels, Bolt-Load Specimen, Standardized Tests, Cracking Threshold			15. NUMBER OF PAGES 29	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE July 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE THERMOCHEMICAL EROSION MODELING OF THE 25-MM M242/M791 GUN SYSTEM				5. FUNDING NUMBERS AMCMS No. 6226.24.H191.1	
6. AUTHOR(S) Samuel Sopok, Peter O'Hara, George Pfielg, Stuart Dunn*, and Douglas Coats* * Software and Engineering Associates, Inc., Carson City, NV					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97017	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 1997 33rd AIAA Joint Propulsion Conference, Seattle, WA, 6-9 July 1997. Published in proceedings of the conference.					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The MACE gun barrel thermochemical erosion modeling code addresses wall degradations due to transformations, chemical reactions, and cracking coupled with pure mechanical erosion for the 25-mm M242/M791 gun system. This predictive tool provides gun system design information that is otherwise impractical. The nitrided A723 and 0.002-inch plated chromium/A723 wall materials are evaluated for erosion using the M242 Cycle A firing scenario. This complex computer analysis is based on rigorously evaluated scientific theory that has been validated in the rocket community over the last forty years. Our gun erosion analysis includes the standard interior ballistics gun code (XNOVAKTC), the standard nonideal gas-wall thermochemical rocket code modified for guns (CCET), the standard mass addition boundary layer rocket code modified for guns (MABL), and the standard wall material ablation conduction erosion rocket code modified for guns (MACE). This analysis provides wall material erosion predictions and comparisons (ablation, conduction, and erosion profiles) as a function of time, travel (customer-selected 6-inch, 12-inch, 30-inch), and number of rounds to barrel condemnation. These M242/M791 gun system predictions agree well with the standard wall heat transfer/temperature profile code (FDHEAT) and actual measured gun system erosion data.					
14. SUBJECT TERMS Modeling Code, Thermochemical Erosion, Gun Barrels, 25-mm M242/M791 Gun System, Ablation, Conduction, Erosion, Chromium, A723 Steel				15. NUMBER OF PAGES 15	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE August 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE DYNAMIC MEASUREMENTS ON THE 120-MM MORTAR BUFFER HOUSING			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. C05370261AFP	
6. AUTHOR(S) Carlos I. Gutierrez and Mario P. Rivera (Union College, Schenectady, NY, and Benet)				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97018	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution limited to U.S. Government Agencies only because of test and evaluation; August 1997. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-DE, Watervliet, NY 12189-4050.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The buffer housing casting proved to be a very costly and difficult part to manufacture. The defect criteria were too restrictive and caused a high percentage of rejections. This dynamic measurements study showed some areas of the casting with low stresses. The defect criteria were modified to accept castings that original criteria would reject.				
14. SUBJECT TERMS Buffer Housing, Mortars, 120-mm Mortars, M120, M121 Mortars, Castings, Defects			15. NUMBER OF PAGES 12	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE RESIDUAL STRESS IN SWAGE AUTOFRETTAGED CYLINDERS WITH AXIAL SEMI-CIRCULAR MID-WALL COOLING CHANNELS				5. FUNDING NUMBERS AMCMS No. 6111.01.91A1	
6. AUTHOR(S) S.L. Lee, J. Neese, and E. Hyland					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97019	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the Society of Experimental Mechanics Spring Conference, Bellevue, WA, 2-4 June 1997. Published in proceedings of the conference.					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) ABAQUS finite element modeling and experimental residual stress mapping have been performed for several swage autofrettaged compound cylinders with semi-circular mid-wall cooling channels. The experimental results verified most features of ABAQUS-predicted stress distributions, except near the bore and at the channel roots, where significantly reduced compressive residual stresses were observed. These observations have been attributed to reverse yielding effect in these areas.					
14. SUBJECT TERMS Autofrettage, Compound Cylinders, Perforated Cylinders, Residual Stress, Reverse Yielding, Bauschinger Effect				15. NUMBER OF PAGES 7	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE INFLUENCE OF THE BAUSCHINGER EFFECT ON RESIDUAL STRESS AND FATIGUE LIFETIMES IN AUTOFRETTAGED THICK-WALLED CYLINDERS				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. TU6A6F361ABJ	
6. AUTHOR(S) Anthony P. Parker (Royal Military College of Science, Cranfield University, Swindon, UK) and John H. Underwood					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97020	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 29th National Fatigue and Fracture Symposium, Stanford University, CA, 24-26 June 1997. Published in ASTM STP Proceedings of the NFFM Symposium.					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This work addresses the influence of Bauschinger effect upon residual stresses and associated fatigue lifetimes for pressurized, autofrettaged thick cylinders. The model employed allows for the variation with radius of Bauschinger Effect Factor (BEF) throughout the autofrettaged tube since the percentage plastic strain, which determines BEF, will vary from a maximum value at the bore to zero at the elastic-plastic interface. Accounting for BEF variability, it is demonstrated that the residual compressive hoop stress at the inner radius of the tube reaches a maximum value at the percentage overstrain level below which reversed yielding does not occur. Existing experimental residual stress measurements from a variety of sources are shown to support this thesis. This value of overstrain may serve to maximize crack initiation lifetime in autofrettaged thick cylinders. For a tube with significant heat-checking and associated initial crack-like defects, it is necessary to consider fatigue crack growth rates governed by a crack growth law such as Paris's Law. For a tube of radius ratio 2.0 and at a value of approximately 40% overstrain, slightly in excess of that for the onset of reversed yielding, the fatigue lifetime exhibits a maximum value. Fatigue lifetimes achieve a maximum value at overstrain levels in which yielding reaches 1.4 times bore radius and are almost constant thereafter. Furthermore, such extended overstrain leads to a small increase in residual stress at the outside diameter (OD), thus increasing R ratio at that location and reducing fatigue lifetime for crack growth originating at the OD. Existing experimental lifetime measurements are shown to require the inclusion of BEF to properly account for these observed lifetimes.					
14. SUBJECT TERMS Bauschinger Effect, Crack Growth, Fatigue Cracks, Fatigue Lifetimes, Cylinders, Fracture (Materials), Fracture Mechanics, Residual Stress, Stress Intensity Factor				15. NUMBER OF PAGES 25	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE HYDROGEN CRACKING DURING SERVICE OF HIGH STRENGTH STEEL CANNON COMPONENTS				5. FUNDING NUMBERS AMCMS No. 6226.24.H191.1	
6. AUTHOR(S) J.H. Underwood, E. Troiano, G.N. Vigilante, A.A. Kapusta, and S. Tauscher					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97021	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 29th National Symposium on Fatigue and Fracture Mechanics, Stanford, CA, 24-26 June 1997. Published in <i>ASTM STP 1332</i> .					
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) An investigation of environmental cracking during service of high strength steel cannon components is described. Two cases of cracking occurred in similar prototypes of an advanced cannon over a two-year period. The materials, components configurations, applied and residual stresses, environmental conditions, and the resulting cracking behaviors and SEM fracture surface characteristics are outlined. Laboratory hydrogen cracking tests of the cannon materials, finite element stress analysis, and stress intensity factor calculations were used to model the hydrogen cracking. The first cracking incident involved cracks up to 21-mm long near a pressure seal in an 1160 MPa yield strength ASTM A723 forged steel cannon tube, following five firing cycles. The second incident involved 50-mm long cracks that had grown after thirty firing cycles near the seal between two adjoining cannon components, one made from A723 and one from 1280 MPa yield strength PH 13-8 Mo stainless steel. The cause of cracking, given the presence of hydrogen-laden propellant products and susceptible high strength steels, was the sustained tensile stresses arising from assembly preloads required to maintain pressure seals between cannon components. Recommended preventative measures include reducing the strength level of the existing martensite steels, changing to austenitic nickel-iron base alloys, and redesign to lower the level of sustained tensile stress concentrations in areas subjected to propellant environments.					
14. SUBJECT TERMS Hydrogen Cracking, Pressure Vessels, High Strength Steel, Environmental Cracking Threshold, Crack Growth Rate, Finite Element Analysis				15. NUMBER OF PAGES 20	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE PERFORMANCE ASSESSMENT OF A SYNERGISTIC GUN BARREL VIBRATION ABSORBER DURING BUMP-COURSE TESTING				5. FUNDING NUMBERS AMCMS No. 6226.24.H191.1	
6. AUTHOR(S) Eric L. Kathe					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97022	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION AVAILABILITY STATEMENT Distribution limited to Department of Defense and Department of Defense contractors because of premature dissemination; September 1997. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-TC, Watervliet, NY 12189-4050.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This report documents the performance of the dynamically tuned shroud vibration absorber—which was designed and constructed at Benet Laboratories—during bump-course testing on a modified M1A1 tank at Aberdeen Proving Ground on 7 March 1997. The dynamically tuned shroud reduces the receptance of the gun barrel to vibrational energy while the tank traverses rough terrain. It is anticipated that this will enhance the accuracy of the weapon system by reducing variation in the initial conditions of gun barrel flexure at the start of launch dynamics. The test results demonstrated that one of the three configurations tested reduced vertical flexure by 24% overall, with a factor of four reduction in the power spectrum amplitude of the first bending mode. Thus, the testing demonstrated that a simple passive approach using existing hardware can significantly enhance the dynamic performance of a weapon system.					
14. SUBJECT TERMS Bump-Course Test, Extended Length Cannon, Dynamics, Accuracy, Vibrations, Time-Frequency, Power Spectrum, M1A1 Abrams Tank				15. NUMBER OF PAGES 80	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT UL	

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE MODAL ANALYSIS OF MORTAR BASEPLATES				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. C04210291AFP	
6. AUTHOR(S) Mario P. Rivera (Union College, Schenectady, NY, and Benet), Elwood Eisler (Union College), and Carlos I. Gutierrez					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97023	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution limited to U.S. Government Agencies only because of test and evaluation; November 1997. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-DE, Watervliet, NY 12189-4050.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The dynamic behavior of mortar baseplates due to shock loading, especially in large caliber mortars, has traditionally led to a number of conjectures among the community of ordnance engineers regarding baseplate structural failure modes such as cracking, gross plastic distortion, etc. Strain field measurements indicate that stress is high with considerable vibration activity of an offensive nature. These events have led to analytical investigations of mortar baseplates using finite element analysis (FEA), with most of these analyses predicting large deformation gradients that have motivated concerns on vibration levels. The manufacture of some baseplates, notably the 120-mm mortar baseplate, is quite laborious. This type of baseplate consists of a monocoque weldment that has more than 64 parts jointed by no less than 100 feet of weld-joints. It follows then that it would be highly advantageous to have simple dynamic acceptance criteria for these baseplates in terms of simple bench instrumented "ringing check-out tests." The purpose of this investigation was to determine and describe the dynamic behavior of the 120-mm mortar baseplate through the use of experimental modal analysis. The information may be used to validate advanced FEA theoretical models relative to the dynamic behavior of these type of structures. The information also may be utilized as a baseline for developing the aforementioned manufacturing "ringing" acceptance criteria for assessing mortar baseplate quality, notably the presence of undesirable defects such as gaps, poor weldments, etc. Our investigation includes the results of more than 200 individual measurements from the structure. The results are presented in computer animation format, as well as the traditional graphical and tabular formats. Finally, the experimental results are compared to theoretical predictions of simplified FEA.					
14. SUBJECT TERMS Modal Analysis, Mortar Baseplates, Vibration of Shells, Fast Fourier Transform Analysis, Computer Animation of Modal Analysis, Experimental Modal Analysis of Shells				15. NUMBER OF PAGES 22	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT III		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 1997		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE THERMAL EFFECTS OF A HOT WEAPON ON HIGH EXPLOSIVE PROJECTILES				5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. TU7Q7F101AFP	
6. AUTHOR(S) Ciro A. Morales III					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050				8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97024	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution limited to U.S. Government Agencies only because of test and evaluation; November 1997. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-DC, Watervliet, NY 12189-4050.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) If a projectile is loaded into a hot cannon tube, the heat from the cannon starts to raise the temperature of the seated round. If not fired quickly (as in a misfire, checkfire, or hangfire situation), the projectile temperatures may increase to a critical point where the high explosive (HE) filler will start to melt, expand, and chemically separate in a process called "exudation." When this occurs, the melted filler becomes more sensitive to detonation, and the rapidly increasing volume of the HE can force the liquid filler out of the fuze threads onto the bore of the hot tube. In the latter event, the probability of an inbore detonation increases dramatically with the possibility of injury to the crew and damage to the cannon platform. This report documents the results of an experiment in which two common 155-mm HE projectiles (the M107 and the rocket-assisted M549A1) were preconditioned to an initial temperature, then rammed into a tube (which itself was preconditioned to a different initial temperature). Time-temperature data for both the projectiles and the tube were gathered, and the reduced data are presented herein.					
14. SUBJECT TERMS Cannon, Cannon Tubes, Projectile, 155-mm M549A1 Projectile, 155-mm M107 Projectile, 155-mm M284 Cannon, High Explosive, Exudation, Thermal Effects				15. NUMBER OF PAGES 39	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE MODELING OF EROSIIVE COMBUSTION PRODUCTS AFFECTING THE 120-MM M256/M829A2 GUN SYSTEM			5. FUNDING NUMBERS AMCMS No. 6226.24.H191.1	
6. AUTHOR(S) Samuel Sopok and Peter O'Hara				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97025	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 34 th JANNAF Combustion Meeting, West Palm Beach, FL, 27-31 October 1997. Published in proceedings of the meeting.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The MACE gun barrel erosion code is used to thermochemically model erosive combustion products affecting the 0.005-inch high contraction (HC) chromium plated A723 steel 120-mm M256/ambient temperature-conditioned M829A2 gun system for a single-round firing scenario. The HC chromium plate, the subsurface A723 steel substrate at HC chromium crack bases, and bare A723 steel are evaluated. This gun erosion analysis includes the standard interior ballistics gun code (XNOVAKTC), the standard nonideal gas-wall thermochemical rocket code modified for guns (CCET), the standard mass addition boundary layer rocket code modified for guns (MABL), and the standard wall material ablation conduction code modified for guns (MACE). Specifically, this new variation of the gun erosion analysis uses MACE wall temperatures as a function of time/position/depth, as well as their associated gas pressures as a function of time/position to thermochemically compute differences in combustion products for the various reacting and nonreacting walls allowing erosive combustion products to be identified. Identification of erosive combustion products by comparative modeling between proposed and present propellant formulations or between a propellant formulation with and without additives may benefit current U.S. Army/Navy programs that attempt to lower propellant flame temperature and/or propellant erosion. Carbon dioxide, water, and carbon monoxide are the identified erosive combustion products for this gun system.				
14. SUBJECT TERMS Gun Erosion Modeling, Erosive Combustion Products, 120-mm M256 Barrels, M829A2 Rounds			15. NUMBER OF PAGES 19	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT U1	

NSN 7540-01-280-5500

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
CHIEF, DEVELOPMENT ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-DA	1
-DB	1
-DC	1
-DD	1
-DE	1
CHIEF, ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-E	1
-EA	1
-EB	1
-EC	1
CHIEF, TECHNOLOGY DIVISION	
ATTN: AMSTA-AR-CCB-T	2
-TA	1
-TB	1
-TC	1
TECHNICAL LIBRARY	
ATTN: AMSTA-AR-CCB-O	5
TECHNICAL PUBLICATIONS & EDITING SECTION	
ATTN: AMSTA-AR-CCB-O	3
OPERATIONS DIRECTORATE	
ATTN: SIOWV-ODP-P	1
DIRECTOR, PROCUREMENT & CONTRACTING DIRECTORATE	
ATTN: SIOWV-PP	1
DIRECTOR, PRODUCT ASSURANCE & TEST DIRECTORATE	
ATTN: SIOWV-QA	1

NOTE: PLEASE NOTIFY DIRECTOR, BENÉT LABORATORIES, ATTN: AMSTA-AR-CCB-O OF ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH AND DEVELOPMENT ATTN: DEPT FOR SCI AND TECH THE PENTAGON WASHINGTON, D.C. 20310-0103	1	COMMANDER ROCK ISLAND ARSENAL ATTN: SMCRI-SEM ROCK ISLAND, IL 61299-5001	1
DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-OC (ACQUISITIONS) 8725 JOHN J. KINGMAN ROAD STE 0944 FT. BELVOIR, VA 22060-6218	2	COMMANDER U.S. ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIBRARY) WARREN, MI 48397-5000	1
COMMANDER U.S. ARMY ARDEC ATTN: AMSTA-AR-AEE, BLDG. 3022	1	COMMANDER U.S. MILITARY ACADEMY ATTN: DEPARTMENT OF MECHANICS WEST POINT, NY 10966-1792	1
AMSTA-AR-AES, BLDG. 321	1	U.S. ARMY MISSILE COMMAND REDSTONE SCIENTIFIC INFO CENTER	2
AMSTA-AR-AET-O, BLDG. 183	1	ATTN: AMSMI-RD-CS-R/DOCUMENTS	
AMSTA-AR-FSA, BLDG. 354	1	BLDG. 4484	
AMSTA-AR-FSM-E	1	REDSTONE ARSENAL, AL 35898-5241	
AMSTA-AR-FSS-D, BLDG. 94	1		
AMSTA-AR-IMC, BLDG. 59	2	COMMANDER U.S. ARMY FOREIGN SCI & TECH CENTER ATTN: DRXST-SD	1
PICATINNY ARSENAL, NJ 07806-5000		220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-DD-T, BLDG. 305	1	COMMANDER U.S. ARMY LABCOM, ISA ATTN: SLCIS-IM-TL	1
ABERDEEN PROVING GROUND, MD 21005-5066		2800 POWER MILL ROAD ADELPHI, MD 20783-1145	
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-WT-PD (DR. B. BURNS)	1		
ABERDEEN PROVING GROUND, MD 21005-5066			

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT'D)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER U.S. ARMY RESEARCH OFFICE ATTN: CHIEF, IPO P.O. BOX 12211 RESEARCH TRIANGLE PARK, NC 27709-2211	1	WRIGHT LABORATORY ARMAMENT DIRECTORATE ATTN: WL/MNM EGLIN AFB, FL 32542-6810	1
DIRECTOR U.S. NAVAL RESEARCH LABORATORY ATTN: MATERIALS SCI & TECH DIV WASHINGTON, D.C. 20375	1	WRIGHT LABORATORY ARMAMENT DIRECTORATE ATTN: WL/MNMF EGLIN AFB, FL 32542-6810	1

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.
